

# Eaton Wash Down EC216



# Part number	Hose ID			Hose OD		Max. Operating pressure		Burst pressure		Max. Bending radius		Weight	
	DN	mm	in	mm	in	bar	psi	bar	psi	mm	in	kg/m	lb/ft
EC216-04BU	6	6.4	0.25	13.4	0.53	400	5800	1600	23200	75	2.94	0.285	0.20
EC216-05BU	8	7.9	0.31	15	0.59	400	5800	1600	23200	85	3.34	0.335	0.23
EC216-06BU	10	9.5	0.38	17.1	0.67	400	5800	1600	23200	90	3.53	0.42	0.29
EC216-08BU	12	12.7	0.5	20.7	0.81	400	5800	1600	23200	130	5.1	0.575	0.40

\*Product also available in GY-Gray

## Construction

- Synthetic rubber tube
- Two wire braids reinforcement
- Oil, abrasion and weather resistant special synthetic rubber smooth cover
- Embossed layline
- Available in blue or grey color cover

## Operating temperature

- 40°C to +150°C (intermittent)\*
- 40°F to +302°F (intermittent)

## Application

High pressure cleaners for food, car wash, labor and swimming bath areas

## Approved fittings

- TTC series
- \* For pressure washer application only